

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



550106

(43) International Publication Date
18 November 2004 (18.11.2004)

PCT

(10) International Publication Number
WO 2004/099524 A1

(51) International Patent Classification⁷: E04C 3/00

(21) International Application Number:
PCT/NO2004/000072

(22) International Filing Date: 18 March 2004 (18.03.2004)

(25) Filing Language: Norwegian

(26) Publication Language: English

(30) Priority Data:
20031367 26 March 2003 (26.03.2003) NO

(71) Applicant and

(72) Inventor: LANGELAND, Bjarte [NO/NO]; Nedre Olav
Nilssonsgate 3, N-4009 Stavanger (NO).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: HINGED AND SEGMENTED PIPE



(57) Abstract: A rigid pipe (1) is achieved according to the invention in that half-cylinder shaped elements (2) are joined/hinged (3) to each other and where to a such chains are connected together with their concave sides in a zipper-like motion. The two half-cylindrical chains are spooled (13) up individually on each side of a housing (12). This result in a particularly rigid pipe of varying length with a wide area of use.

WO 2004/099524 A1